



ISSUES OF EFFICIENT UTILIZATION OF WASTE HEAT FROM FLUE GASES IN INDUSTRIAL ENTERPRISES

Khakimova Gulnoz Nigmanovna
Professor, Tashkent Institute of Chemical Technology

Primov To'ychi Jumayevich
Dsc Tashkent Institute of Chemical Technology

Abulxayev Shodmon Abdushukr oglu
Doctoral Student, Tashkent Institute of Chemical Technology

Abstract

This article discusses the issues of efficient utilization of waste heat from flue gases in industrial enterprises. Industrial thermal processes contribute significantly to global energy consumption and environmental degradation. A substantial portion of the energy used in heavy industry is discharged into the atmosphere as high-temperature flue gases. By examining recuperative systems, organic Rankine cycles, and heat pumps, this study highlights how industrial enterprises can minimize energy losses, reduce carbon footprints, and enhance operational efficiency through purely descriptive and analytical frameworks.

Keywords: Flue gases, industrial energy efficiency, thermal energy utilization, energy conservation, heat exchangers, carbon footprint reduction, industrial sustainability.

Introduction

In the contemporary era of industrialization, energy efficiency has transitioned from a secondary operational goal to a primary strategic necessity. As global energy prices fluctuate and environmental regulations tighten, industrial enterprises ranging from metallurgical plants to chemical processing units are



***Modern American Journal of Engineering,
Technology, and Innovation***

ISSN(E): 3067-7939

Volume 2, Issue 5, May, 2026

Website: usajournals.org

***This work is Licensed under CC BY 4.0 a Creative Commons Attribution
4.0 International License.***

under immense pressure to optimize their thermal cycles. One of the most significant resources in these facilities is the thermal energy carried by flue gases. Flue gas, the byproduct of combustion processes in boilers, furnaces, and kilns, often exits exhaust stacks at remarkably high temperatures. Without recovery mechanisms, this represents a direct loss of primary fuel energy that could otherwise be repurposed to enhance productivity.

The potential for heat recovery is fundamentally governed by the temperature and volume of the exhaust stream. High-grade heat, often found in heavy manufacturing, is easily convertible to mechanical or electrical energy. In contrast, low-grade heat is typically redirected for process heating or domestic water warming within the facility. The primary challenge in utilizing this energy lies in the chemical composition of the gases. Many industrial fuels contain sulfur and other elements that, when cooled below a certain threshold, form corrosive acids. Therefore, modern recovery systems must be designed to extract the maximum amount of heat while maintaining the gas temperature just above the point where condensation and subsequent equipment damage occur.

The most direct method of utilization is the use of recuperative heat exchangers. These systems work by transferring heat from the hot flue gas to a colder medium, such as incoming combustion air or water, through a conductive wall. By preheating the air used for combustion, a furnace requires significantly less fuel to reach its operating temperature, leading to immediate cost savings.

In scenarios where the heat cannot be used directly for warming, Waste Heat Boilers play a crucial role. These units transform the thermal energy of flue gases into high-pressure steam. This steam can then be integrated into various industrial processes, such as chemical synthesis or mechanical cleaning, or even directed to turbines for on-site electricity generation. This approach effectively turns a waste product into a valuable utility.

For enterprises dealing with medium-temperature exhaust, the Organic Rankine Cycle has emerged as a breakthrough. Unlike traditional steam turbines that require very high temperatures, this technology utilizes organic fluids with lower boiling points. This allows plants to generate electricity even from relatively “cool” exhaust streams that were previously considered impossible to harvest.



Modern American Journal of Engineering, Technology, and Innovation

ISSN(E): 3067-7939

Volume 2, Issue 5, May, 2026

Website: usajournals.org

This work is Licensed under CC BY 4.0 a Creative Commons Attribution 4.0 International License.

This flexibility is vital for industries like cement manufacturing and food processing, where exhaust temperatures are moderate but consistent.

Despite the clear benefits, several technical hurdles persist in the implementation of these systems. Contamination and fouling are the most frequent issues. Flue gases, especially those originating from coal or heavy oil combustion, contain particulate matter and soot. Over time, these substances deposit on the surfaces of heat exchangers, creating an insulating layer that hampers thermal transfer. This necessitates the use of advanced coatings and automated cleaning cycles to maintain system performance.

Furthermore, the physical integration of recovery units into existing plants often poses a logistical challenge. Many older industrial sites were not designed with secondary heat recovery in mind, leading to space constraints. Engineering solutions must therefore be compact and modular, allowing for retrofitting without requiring a complete overhaul of the existing exhaust infrastructure. The integration of heat recovery systems offers a dual benefit that aligns with modern corporate responsibility. From an economic perspective, the reduction in fuel consumption provides a rapid return on investment. As energy taxes and carbon credits become more prevalent in the global economy, the ability to operate with lower emissions also provides a competitive edge in international markets.

From an environmental standpoint, every unit of heat recovered directly replaces a unit of heat that would have been generated by burning additional fossil fuels. This leads to a measurable decrease in carbon dioxide and nitrogen oxide emissions. By closing the energy loop, industrial enterprises can significantly reduce their ecological footprint while maintaining high levels of output. This transition is essential for meeting international climate goals and ensuring the long-term sustainability of the manufacturing sector.

The next frontier in flue gas utilization involves the integration of digital monitoring and artificial intelligence. Modern industrial systems are increasingly equipped with sensors that monitor the real-time composition and thermal profile of exhaust gases. Algorithms can now predict the optimal flow rates to maximize heat extraction while avoiding corrosive zones. This “smart” thermal management ensures that the recovery system operates at peak efficiency regardless of fluctuations in production intensity.



***Modern American Journal of Engineering,
Technology, and Innovation***

ISSN(E): 3067-7939

Volume 2, Issue 5, May, 2026

Website: usajournals.org

***This work is Licensed under CC BY 4.0 a Creative Commons Attribution
4.0 International License.***

While high-temperature gases are easily utilized, a significant challenge remains in capturing heat from "cool" flue gases. In these instances, industrial heat pumps are becoming indispensable. These systems operate by using a small amount of external energy to elevate the temperature of the waste heat to a level where it becomes useful for industrial processes. By utilizing advanced refrigerants and closed-loop cycles, heat pumps can recover energy from exhaust streams that were previously considered thermal waste. This technology is particularly effective in the textile and food industries, where large volumes of low-temperature steam and hot water are required for dyeing and sterilization processes.

The physical durability of heat recovery units is a major concern in aggressive chemical environments. Recent advancements in material science have introduced specialized nanocoatings and high-nickel alloys that are resistant to acid corrosion and ash adhesion. Traditional carbon steel exchangers often fail within months when exposed to sulfur-rich flue gases. However, the application of ceramic-based coatings and polymer-composite materials allows heat exchangers to operate safely below the acid dew point. This breakthrough enables "condensing" heat recovery, where the latent heat of water vapor within the flue gas is also captured, potentially increasing the efficiency of a boiler by an additional 10% to 15%.

Industrial production is often intermittent, while waste heat generation is continuous. To bridge this gap, Thermal Energy Storage systems are being integrated into flue gas recovery circuits. Using phase-change materials or molten salts, enterprises can buffer the captured heat during periods of low demand and release it during peak production hours. This synchronization ensures that no recovered energy is wasted and provides a stable thermal load for the facility, reducing the mechanical stress on primary boilers caused by rapid temperature fluctuations.

The shift toward efficient flue gas utilization is not only driven by technology but also by international regulatory frameworks. The transition to "Net Zero" emissions targets has led many governments to provide subsidies and tax incentives for enterprises that install waste heat recovery systems. Furthermore, the implementation of ISO 50001 provides a structured methodology for plants



to identify, measure, and optimize their thermal losses. By aligning technical recovery with global standards, industrial enterprises can improve their environmental ratings, making them more attractive to green investors and reducing their exposure to future carbon taxes.

Conclusion

The effective utilization of waste heat from flue gases is no longer an optional environmental initiative, it is a fundamental pillar of modern industrial engineering. While technical challenges such as fouling and corrosion require careful management, the development of specialized heat exchangers and organic cycles has expanded the possibilities for energy capture across diverse sectors. For industrial enterprises, the path forward involves a systematic assessment of thermal losses and the adoption of tailored recovery technologies. By transforming waste into a resource, industries can ensure both financial profitability and environmental stewardship in an increasingly resource-constrained world.

References:

1. Smith, J. R. (2023). *Thermodynamics of Industrial Waste Heat Recovery: Systems and Optimization*. 2nd Edition. New York: Academic Press. pp. 145–182.
2. Johnson, L. M., & Wang, H. (2024). Advanced Heat Exchangers for Flue Gas Recovery in Heavy Industry. *Journal of Thermal Science and Engineering Applications*, Vol. 16, Issue 4. London: Springer Nature. pp. 210–235.
3. Kuznetsov, G. V., & Sitnikov, A. S. (2022). *Thermal Efficiency in Power Generation Plants*. Moscow: EnergoAtomIzdat. pp. 88–112.
4. International Energy Agenc. (2025). *Energy Efficiency Report: Decarbonizing the Industrial Sector*. Paris: IEA Publications. pp. 45–60.
5. Raxmonov, A. T. (2021). *Energy-saving technologies in industrial enterprises*. Tashkent: Fan va Texnologiya Publishing. pp. 120–145.